



Corrlube-653

Cutting / Grinding Liquid

Description:

Corrlube-653 offers one pack, multi functional, water dilute able, synthetic grinding liquid with special additives, which develop for general grinding and tooling.

Key Features:

- Control frictional heat generation under extreme pressure metal working conditions.
- Guards both the cutting metal and working tools and prolongs there working life.
- It contains corrosion inhibitors to protect parts, equipments and tools.
- It forms a clear liquid, which allows the work good visibility of the parts
- Improved drill and tap life
- Excellent bio-stability minimizes the need for additives
- Reduced annual disposal costs
- Cleaner machine reduces maintenance and costs related to down-time
- Low foam levels, even on high pressure systems
- Outstanding protection against rust and corrosion
- Potassium Dichromate free

Instructions of Use:

- Fill tank with De Ionized water first before adding Corrlube-653.
- Mix 1% to 3% of the De Ionized water for general grinding.

Economical:

- Corrlube-653 solutions have a long working life and is very economical in use

Typical Specifications:

- | | |
|-------------------------------------|---------------------------|
| • Appearance | Yellow Transparent Liquid |
| • Density | 1.06 – 1.1 |
| • pH | 9 – 10.5 |
| • Solubility in Water (% by Weight) | 100 |

Health and safety:

- In case of contact with eyes, flood eye with plenty of water.
- Incase of ingestion, wash out mouth with water, do not induce vomiting and seek medical help.

Recommendation: Use De Ionized water only